

**Description**

Fastener Length: 4-37/64", Thread: 3/8-24, Thread Length: 9/16", NAS6606 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS660664
Minimum Qty (MOQ):	1
NSN:	5306-01-477-6653
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6606-64 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.578 Inches Nominal
<b>Fastener Length:</b>	4.563 Inches Minimum And 4.593 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.173 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.554 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>End Item Identification:</b>	Target Radar System
<b>Nominal Thread Diameter:</b>	0.3750 Inches
<b>Grip Length:</b>	3.990 Inches Minimum And 4.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Special Features:</b>	Per Mil-h-6875, Heat Treatment Will Be 160-180 Ksi Ft <sub>u</sub> ; 95 Ksi Minimum Ultimate Shear
<b>Material:</b>	Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.