

Description

Fastener Length: 4-37/64", Thread: 3/8-24, Thread Length: 9/16", NAS6606 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660664
Minimum Qty (MOQ):	1
NSN:	5306-01-477-6653
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6606-64 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	4.563 Inches Minimum And 4.593 Inches Maximum
Head Style:	Hexagon
Head Height:	0.173 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
End Item Identification:	Target Radar System
Nominal Thread Diameter:	0.3750 Inches
Grip Length:	3.990 Inches Minimum And 4.010 Inches Maximum
Thread Quantity Per Inch:	24
Special Features:	Per Mil-h-6875, Heat Treatment Will Be 160-180 Ksi Ft _u ; 95 Ksi Minimum Ultimate Shear
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.