

Description

Thread: 3/8-3A, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660667
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-606-5536
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6606-67 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.578 Inches Nominal
<b>Fastener Length:</b>	4.938 Inches Minimum And 4.968 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.163 Inches Minimum And 0.188 Inches Maximum
<b>Width Between Flats:</b>	0.554 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.3750 Inches
<b>Grip Length:</b>	4.365 Inches Minimum And 4.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	3a
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Shear
<b>Special Features:</b>	Bolt, Shear
<b>Material:</b>	Steel Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606-67> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.