

Description

Thread: 3/8-3A, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS660667
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-606-5536
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6606-67 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	4.938 Inches Minimum And 4.968 Inches Maximum
Head Style:	Hexagon
Head Height:	0.163 Inches Minimum And 0.188 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.3750 Inches
Grip Length:	4.365 Inches Minimum And 4.385 Inches Maximum
Thread Quantity Per Inch:	3a
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt, Shear
Special Features:	Bolt, Shear
Material:	Steel Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606-67> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.