

Description

length: 2.390", grip: 1.812", thread: 3/8-24, hex head - drilled shank - tension - long thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6606D29
Minimum Qty (MOQ):	2
NSN:	5306-01-354-4676
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6606D29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	2.375 Inches Minimum And 2.405 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.802 Inches Minimum And 1.822 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.193 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6606 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.