

Description

Fastener Length: 3-21/64", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6606D44
Minimum Qty (MOQ):	5
NSN:	5306-01-576-3743
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6606D44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	3.313 Inches Minimum And 3.343 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.173 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Nominal Mils And 0.564 Nominal Centimeters
Grip Diameter:	0.374 Nominal Mils And 0.375 Nominal Centimeters
Shank Unthreaded Hole Diameter:	0.106 Nominal Mils Overall And 0.116 Nominal Centimeters Overall
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.740 Nominal Mils And 2.760 Nominal Centimeters
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.131 Inches Nominal Overall
Part Name Assigned By Controlling Agency:	Bolt,tension,hex Head,close Tolerance,alloy Steel,long Thread,reduced Major Dia,nonlocking, 160 Ksi FtU
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Ams6349 Assn Std Single Material Response Overall Or Ams6340 Assn Std Single Material Response Overall Or Ams 6415 Assn Std Single Material Response Overall Or Ams 6484 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416 Type II Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.