

Description

Fastener Length: 3-45/64", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6606D50
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-588-5197
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6606D50 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	3.688 Inches Minimum And 3.718 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.544 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.370 Inches Nominal
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	3.125 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.506 Inches Nominal Overall
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Long Thread, Reduced Major Diameter, Self-locking, 160 Ksi FtU
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6606 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D50> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.