

Description

Fastener Length: 3-45/64", Thread: 3/8-24, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS6606D50       |
| Minimum Qty (MOQ): | 1 EA             |
| NSN:               | 5306-01-588-5197 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N NAS6606D50 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.578 Inches Nominal  |
| <b>Fastener Length:</b>   | 3.688 Inches Minimum And 3.718 Inches Maximum   |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.188 Inches Minimum And 0.203 Inches Maximum   |
| <b>Width Between Flats:</b>   | 0.544 Inches Minimum And 0.564 Inches Maximum   |
| <b>Grip Diameter:</b>   | 0.370 Inches Nominal  |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Nominal First Hole   |
| <b>Nominal Thread Diameter:</b>   | 0.375 Inches  |
| <b>Grip Length:</b>   | 3.125 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>  | 24  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch   |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 3.506 Inches Nominal Overall  |
| <b>Part Name Assigned By Controlling Agency:</b>                        | Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Long Thread, Reduced Major Diameter, Self-locking, 160 Ksi Ft <sub>u</sub> |
| <b>Material:</b>  | Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall   |
| <b>Thread Series Designator:</b>  | Unjf  |
| <b>Specification/standard Data:</b>                                     | 80205-nas6606 Professional/industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D50> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.