

**Description**

Fastener Length: 1-5/64", Thread: 3/8-24, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6606D8
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-438-8255
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS6606D8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.5720 Inches Nominal
<b>Fastener Length:</b>	1.0630 Inches Minimum And 1.0930 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.1880 Inches Minimum And 0.2030 Inches Maximum
<b>Width Between Flats:</b>	0.5540 Inches Minimum And 0.5640 Inches Maximum
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.3750 Inches
<b>Grip Length:</b>	0.4900 Inches Minimum And 0.5100 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6606d8 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.