

Description

Fastener Length: 5-37/64", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6606D80
Minimum Qty (MOQ):	2
NSN:	5306-01-438-8258
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6606D80 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.572 Inches Nominal
Fastener Length:	5.557 Inches Minimum And 5.587 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.1880 Inches Minimum And 0.2030 Inches Maximum
Width Between Flats:	0.5540 Inches Minimum And 0.5640 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	4.9900 Inches Minimum And 5.0100 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6606d80 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.