



★ FASTENERS

Military-Fasteners.com

P/N NAS6606D80

Description

Fastener Length: 5-37/64", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6606D80 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-438-8258 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS6606D80 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.572 Inches Nominal |
| Fastener Length: | 5.557 Inches Minimum And 5.587 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.1880 Inches Minimum And 0.2030 Inches Maximum |
| Width Between Flats: | 0.5540 Inches Minimum And 0.5640 Inches Maximum |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 4.9900 Inches Minimum And 5.0100 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6606d80 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606D80> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.