

# P/N NAS6606H12

Military-Fasteners.com

#### Description

length: 1.328", grip: 0.75", thread: 3/8-24, hex head, drilled head, tension, long thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS6606H12                                |
|-------------------------|---|
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-285-9977                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6606H12 Specifications

| Thread Class:                                     | За   |
|---|--|
| Thread Direction:                                 | Right-hand   |
| Thread Length:                                    | 0.553 Inches Minimum And 0.603 Inches Maximum  |
| Fastener Length:                                  | 1.313 Inches Minimum And 1.343 Inches Maximum  |
| Head Style:                                       | Dished Hexagon   |
| Head Height:                                      | 0.188 Inches Minimum And 0.203 Inches Maximum  |
| Width Between Flats:                              | 0.554 Inches Minimum And 0.564 Inches Maximum  |
| Hole Diameter:                                    | 0.070 Inches Minimum And 0.080 Inches Maximum  |
| Grip Diameter:                                    | 0.3735 Inches Minimum And 0.3745 Inches Maximum  |
| Nominal Thread Diameter:                          | 0.375 Inches   |
| Grip Length:                                      | 0.740 Inches Minimum And 0.760 Inches Maximum  |
| Hole Quantity:                                    | 3  |
| Hole Type:  | Drilled  |
| Thread Quantity Per Inch:                         | 24   |
| Minimum Tensile Strength:                         | 160000 Pounds Per Square Inch  |
| Hole Configuration Style:                         | Hexagon Corners  |
| Surface Finish:                                   | 32.0 Microinches Bearing Surface Of Head   |
| Surface Finish:                                   | 32.0 Microinches Grip  |
| Surface Finish:                                   | 32.0 Microinches Threads   |
| Material:   | Steel Comp E4340 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification:             | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std<br>2nd Material Response Overall |
| Surface Treatment:                                | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And<br>Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                         | Unjf   |
| Specification/standard Data:                      | 80205-nas6606 Professional/industrial Association Standard   |
|   |  |

### How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6606H12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.