

**Description**

length: 2.078", grip: 1.500", thread: 3/8-24, hex head, drilled head, tension, long thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6606H24
Minimum Qty (MOQ):	10
NSN:	5306-01-386-3892
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

# P/N NAS6606H24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.578 Inches Nominal
<b>Fastener Length:</b>	2.063 Inches Minimum And 2.093 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.554 Inches Minimum And 0.564 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.490 Inches Minimum And 1.510 Inches Maximum
<b>Hole Quantity:</b>	3
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Hexagon Corners
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2,cI 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6606 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606H24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.