

P/N NAS6606H27

Description

length: 2.266", grip: 1.688", thread: 3/8-24, hex head, drilled head, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6606H27

Minimum Qty (MOQ): 5

NSN: 5306-01-385-6139

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6606H27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	2.251 Inches Minimum And 2.281 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.374 Inches Minimum And 0.375 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.688 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hole Configuration Style:	Hexagon Corners
Special Features:	Shall Be In Accordance With All Requirements As Specified In National Aerospace Standard Nas 6603 Through 6620
Material:	Steel Comp E4340 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6606 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6606H27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.