

Description

Fastener Length: 2-33/64", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6606H31 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-386-5296 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS6606H31 Specifications

| | |
|-------------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.578 Inches Nominal |
| Fastener Length: | 2.516 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Nominal |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.374 Inches Minimum And 0.375 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.938 Inches Nominal |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Hole Configuration Style: | Hexagon Corners |
| Special Features: | Shall Be In Accordance With All Requirements As Specified In National Aerospace Standard Nas 6603 Through 6620 |
| Material: | Steel Comp E4340 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6606 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606H31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.