

**Description**

Fastener Length: 2-25/64", Thread: 7/16-20, Thread Length: 11/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS660727
Minimum Qty (MOQ):	2
NSN:	5306-01-439-1186
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS6607-27 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.6940 Inches Nominal
<b>Fastener Length:</b>	2.367 Inches Minimum And 2.397 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.2190 Inches Minimum And 0.2340 Inches Maximum
<b>Width Between Flats:</b>	0.6780 Inches Minimum And 0.6900 Inches Maximum
<b>Grip Diameter:</b>	0.4360 Inches Minimum And 0.4370 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.4375 Inches
<b>Grip Length:</b>	1.6780 Inches Minimum And 1.6980 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6607-27 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.