

Description

Fastener Length: 2-25/64", Thread: 7/16-20, Thread Length: 11/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660727
Minimum Qty (MOQ):	2
NSN:	5306-01-439-1186
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6607-27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.6940 Inches Nominal
Fastener Length:	2.367 Inches Minimum And 2.397 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.2190 Inches Minimum And 0.2340 Inches Maximum
Width Between Flats:	0.6780 Inches Minimum And 0.6900 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	1.6780 Inches Minimum And 1.6980 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6607-27 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.