



Military-Fasteners.com

P/N NAS6607-50

Description

Fastener Length: 3-53/64", Thread: 3/8-20, Thread Length: 11/16", NAS6607 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660750
Minimum Qty (MOQ):	2
NSN:	5306-01-356-9466
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6607-50 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	3.804 Inches Minimum And 3.834 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.194 Inches Minimum And 0.219 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.437 Inches
Grip Length:	3.115 Inches Minimum And 3.135 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,cl 2,ty 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6607 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607-50> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.