

Description

Fastener Length: 1-33/64", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6607D13
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-354-7715
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS6607D13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	1.491 Inches Minimum And 1.521 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.184 Inches Minimum And 0.214 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.437 Inches Minimum And 0.460 Inches Maximum
Shank Unthreaded Hole Diameter:	0.201 Inches Nominal First Hole
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.802 Inches Minimum And 0.812 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.305 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Grip32.0 Microinches Threads32.0 Microinches Fastener
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416a Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6607 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607D13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.