

Description

Fastener Length: 1-33/64", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6607D13 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-354-7715 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6607D13 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.694 Inches Nominal |
| Fastener Length: | 1.491 Inches Minimum And 1.521 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.184 Inches Minimum And 0.214 Inches Maximum |
| Width Between Flats: | 0.678 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.437 Inches Minimum And 0.460 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.201 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 0.802 Inches Minimum And 0.812 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.305 Inches Nominal First Hole |
| Surface Finish: | 32.0 Microinches Grip32.0 Microinches Threads32.0 Microinches Fastener |
| iii Part Name Assigned By Controlling Agency: | Navy Special Project |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416a Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6607 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607D13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.