



Military-Fasteners.com

P/N NAS6607D22

Description

Fastener Length: 2-5/64", Thread: 7/16-20, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6607D22 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-437-9250 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6607D22 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.669 Inches Minimum And 0.719 Inches Maximum |
| Fastener Length: | 2.054 Inches Minimum And 2.084 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.219 Inches Minimum And 0.234 Inches Maximum |
| Width Between Flats: | 0.678 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.4360 Inches Minimum And 0.4370 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.968 Inches Nominal First Hole |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6069 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6607 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607D22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.