

Description

Fastener Length: 4-1/16", Thread: 3/8-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6607D69 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-483-0212 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N NAS6607D69 Specifications

| | |
|----------------------------------|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.694 Inches Nominal |
| Fastener Length: | 4.069 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.219 Inches Nominal |
| Width Between Flats: | 0.678 Inches Minimum And 0.690 Inches Maximum |
| Grip Diameter: | 0.435 Inches Minimum And 0.436 Inches Maximum |
| Nominal Thread Diameter: | 0.437 Inches |
| Grip Length: | 5.319 Inches Nominal |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607D69> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.