

Description

Fastener Length: 2-1/16", Hole Diameter: 3/32", Thread: 3/8-20, Thread Length: 11/16", NAS6607 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6607DH22
Minimum Qty (MOQ):	2
NSN:	5306-01-598-9824
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6607DH22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	2.069 Inches Nominal
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Hole Diameter:	0.106 Inches Nominal
Grip Diameter:	0.436 Inches Minimum And 0.437 Inches Maximum
Point Diameter:	0.426 Inches Minimum And 0.431 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.375 Nominal Inches
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6349 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607DH22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.