

Description

Fastener Length: 1-3/4", Thread: 3/8-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6607H17
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-386-3194
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6607H17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	1.756 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.436 Inches Minimum And 0.437 Inches Maximum
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.062 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Hole Configuration Style:	Hexagon Corners
Special Features:	Shall Be In Accordance With All Requirements As Specified In National Aerospace Standard Nas 6603 Through 6620
Material:	Steel Comp E4340 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6607 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607H17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.