

**Description**

Fastener Length: 7/8", Thread: 7/16-20, Thread Length: 11/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6607H3
Minimum Qty (MOQ):	5
NSN:	5306-01-615-0799
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS6607H3 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.694 Inches Nominal
<b>Fastener Length:</b>	0.882 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.219 Inches Nominal
<b>Width Between Flats:</b>	0.678 Inches Minimum And 0.690 Inches Maximum
<b>Grip Diameter:</b>	0.426 Inches Minimum And 0.431 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.4375 Inches
<b>Grip Length:</b>	0.188 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4140 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.