

Description

Fastener Length: 7/8", Thread: 7/16-20, Thread Length: 11/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6607H3
Minimum Qty (MOQ):	5
NSN:	5306-01-615-0799
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6607H3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	0.882 Inches Nominal
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.426 Inches Minimum And 0.431 Inches Maximum
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	0.188 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6607H3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.