

**Description**

Right hand, shear, NAS6608 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS660813
Minimum Qty (MOQ):	5
NSN:	5306-01-214-5956
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6608-13 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.710 Inches Minimum And 0.760 Inches Maximum
<b>Fastener Length:</b>	1.532 Inches Minimum And 1.562 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4985 Inches Minimum And 0.4995 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	0.802 Inches Minimum And 0.822 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp E4340 Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6608 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.