

Description

Right hand, shear, NAS6608 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660813
Minimum Qty (MOQ):	5
NSN:	5306-01-214-5956
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6608-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.710 Inches Minimum And 0.760 Inches Maximum
Fastener Length:	1.532 Inches Minimum And 1.562 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6608 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.