

P/N NAS6608-21X

Description

Fastener Length: 2-1/16", Thread: 1/2-20, Thread Length: 3/4", NAS6608 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS660821X

Minimum Qty (MOQ):

NSN: 5306-01-280-5676

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS6608-21X Specifications

3a
Right-hand
0.710 Inches Minimum And 0.760 Inches Maximum
2.032 Inches Minimum And 2.062 Inches Maximum
Dished Hexagon
0.250 Inches Minimum And 0.265 Inches Maximum
0.741 Inches Minimum And 0.752 Inches Maximum
0.5141 Inches Minimum First Shoulder And 0.5151 Inches Maximum First Shoulder
1.302 Inches Minimum First Shoulder And 1.322 Inches Maximum First Shoulder
0.500 Inches
20
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Round First Shoulder
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6608 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6608-21X and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.