

## **P/N NAS6608-25**

### **Description**

NAS6608-25 Shear Bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS660825

Minimum Qty (MOQ):

NSN: 5306-01-156-5104

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6608-25 Specifications**

| Thread Class:                                  | 3a  |
|--|---|
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 0.710 Inches Minimum And 0.760 Inches Maximum   |
| Fastener Length:                               | 2.282 Inches Minimum And 2.312 Inches Maximum   |
| Head Style:                                    | Dished Hexagon  |
| Head Height:                                   | 0.250 Inches Minimum And 0.265 Inches Maximum   |
| Width Between Flats:                           | 0.741 Inches Minimum And 0.752 Inches Maximum   |
| Grip Diameter:                                 | 0.4985 Inches Minimum And 0.4995 Inches Maximum   |
| Nominal Thread Diameter:                       | 0.500 Inches  |
| Grip Length:                                   | 1.552 Inches Minimum And 1.572 Inches Maximum   |
| Thread Quantity Per Inch:                      | 20  |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch   |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head  |
| Surface Finish:                                | 32.0 Microinches Grip   |
| Surface Finish:                                | 32.0 Microinches Threads  |
| Material:                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall   |
| Material Document And Classification:          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall  |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                      | Unjf  |
| Specification/standard Data:                   | 80205-nas6608 Professional/industrial Association Standard  |
|  |   |

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6608-25">https://military-fasteners.com/bolts/shear+bolts/NAS6608-25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6608-25">https://military-fasteners.com/bolts/shear+bolts/NAS6608-25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6608-25">https://military-fasteners.com/bolts/shear+bolts/NAS6608-25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6608-25">https://military-fasteners.com/bolts/shear+bolts/NAS6608-25</a> and selecting the quantity you want then