

**Description**

Fastener Length: 2-35/64", Thread: 1/2-20, Thread Length: 3/4",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS660828                                 |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-398-1752                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6608-28 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.735 Inches Nominal   |
| <b>Fastener Length:</b>                               | 2.532 Inches Minimum And 2.562 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.250 Inches Minimum And 0.265 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.741 Inches Minimum And 0.752 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.4985 Inches Minimum And 0.4995 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.500 Inches   |
| <b>Grip Length:</b>                                   | 1.740 Inches Minimum And 1.760 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 20   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Head  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416a Tyii Cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas6608 Professional/industrial Association Standard   |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.