

## P/N NAS6608-31

### **Description**

NAS6608-31 Close Tolerance Bolt

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS660831

Minimum Qty (MOQ):

NSN: 5306-01-494-5773

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6608-31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	2.658 Inches Minimum And 2.688 Inches Maximum
Head Style:	Hexagon
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4945 Inches Minimum And 0.4950 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.923 Inches Minimum And 1.953 Inches Maximum
Thread Quantity Per Inch:	20
Material:	Steel Comp 4140 Overall And Steel Comp 4340 Overall And Steel Comp E4340 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall And Ams6415 Assn Std 2nd Material Response Overall And Mil-s-5000 Mil Spec 3rd Material Response Overall And Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6608-31">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6608-31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.