

P/N NAS6608-38

Description

Fastener Length: 3-1/8", Thread: 1/2-20, Thread Length: 3/4",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS660838

Minimum Qty (MOQ):

NSN: 5306-01-267-1122

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6608-38 Specifications

3a
Right-hand
0.710 Inches Minimum And 0.760 Inches Maximum
3.095 Inches Minimum And 3.125 Inches Maximum
Dished Hexagon
0.250 Inches Minimum And 0.265 Inches Maximum
0.741 Inches Minimum And 0.752 Inches Maximum
0.4985 Inches Minimum And 0.4995 Inches Maximum
0.500 Inches
2.365 Inches Minimum And 2.385 Inches Maximum
20
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6608 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6608-38 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6608-38 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6608-38 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6608-38 and selecting the quantity you want then