

Description

Fastener Length: 1-13/16", Thread: 1/2-20, Thread Length: 47/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6608D17
Minimum Qty (MOQ):	5
NSN:	5306-01-439-1187
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6608D17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.7350 Inches Nominal
Fastener Length:	1.7820 Inches Minimum And 1.8120 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.2500 Inches Minimum And 0.2650 Inches Maximum
Width Between Flats:	0.7410 Inches Minimum And 0.7520 Inches Maximum
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.5000 Inches
Grip Length:	1.0520 Inches Minimum And 1.0720 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6608d17 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608D17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.