

**Description**

Fastener Length: 1-13/16", Thread: 1/2-20, Thread Length: 47/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6608D17
Minimum Qty (MOQ):	5
NSN:	5306-01-439-1187
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N NAS6608D17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.7350 Inches Nominal
<b>Fastener Length:</b>	1.7820 Inches Minimum And 1.8120 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.2500 Inches Minimum And 0.2650 Inches Maximum
<b>Width Between Flats:</b>	0.7410 Inches Minimum And 0.7520 Inches Maximum
<b>Grip Diameter:</b>	0.4985 Inches Minimum And 0.4995 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.5000 Inches
<b>Grip Length:</b>	1.0520 Inches Minimum And 1.0720 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6608d17 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608D17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.