

**Description**

Fastener Length: 2-1/2", Thread: 31/64-20, Thread Length: 47/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6608D28
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-464-2664
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS6608D28 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.735 Inches Nominal
<b>Fastener Length:</b>	2.470 Inches Minimum And 2.500 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.500 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.491 Inches
<b>Grip Length:</b>	1.740 Inches Minimum And 1.760 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Hex Head, Close Tolerance, Alloy Steel, Long Thread, Self-locking And Nonlocking
<b>Material:</b>	Steel Comp 4140 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty2cl2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608D28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.