

Description

Fastener Length: 2-3/4", Hole Diameter: 1/16", Thread: 1/2-20, Thread Length: 47/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6608D32
Minimum Qty (MOQ):	5
NSN:	5306-01-412-1237
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6608D32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.630 Inches Minimum And 0.740 Inches Maximum
Fastener Length:	2.720 Inches Minimum And 2.750 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.4945 Inches Minimum And 0.4950 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608D32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.