

P/N NAS6608D42

Description

Fastener Length: 3-1/8", Thread: 1/2-20, Thread Length: 3/4", NAS6608 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6608D42

Minimum Qty (MOQ):

NSN: 5306-01-481-5082

Schedule B: 7318.15.8085

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N NAS6608D42 Specifications

Thread Direction: Right-hand Thread Length: 0.710 Inches Minimum And 0.760 Inches Maximum Fastener Length: 3.095 Inches Minimum And 3.125 Inches Maximum Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Thread Length: 0.710 Inches Minimum And 0.760 Inches Maximum 3.095 Inches Minimum And 3.125 Inches Maximum Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 0.000 Pounds Per Square Inch
Fastener Length: Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 0.000 Pounds Per Square Inch
Head Style: Dished Hexagon Head Height: 0.250 Inches Minimum And 0.265 Inches Maximum Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Head Height: Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Width Between Flats: 0.741 Inches Minimum And 0.752 Inches Maximum Grip Diameter: 0.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Grip Diameter: O.4985 Inches Minimum And 0.4995 Inches Maximum Shank Unthreaded Hole Diameter: O.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Nominal Thread Diameter: O.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Shank Unthreaded Hole Diameter: Nominal Thread Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole 0.500 Inches Grip Length: 2.615 Inches Minimum And 2.635 Inches Maximum Thread Quantity Per Inch: 20 Minimum Tensile Strength: 160000 Pounds Per Square Inch
Nominal Thread Diameter:0.500 InchesGrip Length:2.615 Inches Minimum And 2.635 Inches MaximumThread Quantity Per Inch:20Minimum Tensile Strength:160000 Pounds Per Square Inch
Grip Length:2.615 Inches Minimum And 2.635 Inches MaximumThread Quantity Per Inch:20Minimum Tensile Strength:160000 Pounds Per Square Inch
Thread Quantity Per Inch: Minimum Tensile Strength: 20 160000 Pounds Per Square Inch
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center: 2.879 Inches Minimum First Hole And 2.919 Inches Maximum First Hole
Surface Finish: 32.0 Microinches Bearing Surface Of Head
Surface Finish: 32.0 Microinches Grip
Surface Finish: 32.0 Microinches Threads
Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6608D42 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6608D42 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6608D42 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6608D42 and selecting the quantity you want then