



Military-Fasteners.com

P/N NAS6608D60

Description

Fastener Length: 4-1/2", Thread: 1/2-20, Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6608D60
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-588-5206
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6608D60 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	4.485 Inches Minimum And 4.500 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Minimum And 0.265 Inches Maximum
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.510 Inches Nominal
Nominal Thread Diameter:	0.500 Inches
Grip Length:	3.750 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hexz Head, Close Tolerance, Alloy Steel, Long Thread, Reduced Major Diameter, Self-locking, 160 Ksi FtU
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6608 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6608D60> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.