

Description

Fastener Length: 2-1/2", Thread: 9/16-18, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660927
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-537-4389
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6609-27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	2.528 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.281 Inches Minimum And 0.296 Inches Maximum
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.5565 Inches Minimum And 0.5570 Inches Maximum
Nominal Thread Diameter:	0.5625 Inches
Grip Length:	1.688 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	16000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Ams6415 Assn Std 4th Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6609-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.