

**Description**

Fastener Length: 2-1/2", Thread: 9/16-18, Thread Length: 13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS660927
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-537-4389
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS6609-27 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.840 Inches Nominal
<b>Fastener Length:</b>	2.528 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.281 Inches Minimum And 0.296 Inches Maximum
<b>Width Between Flats:</b>	0.865 Inches Minimum And 0.877 Inches Maximum
<b>Grip Diameter:</b>	0.5565 Inches Minimum And 0.5570 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.5625 Inches
<b>Grip Length:</b>	1.688 Inches Nominal
<b>Thread Quantity Per Inch:</b>	18
<b>Minimum Tensile Strength:</b>	16000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Ams6415 Assn Std 4th Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6609-27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.