



Military-Fasteners.com

P/N NAS6609D24

Description

Fastener Length: 2-5/16", Thread: 1/2-18, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6609D24
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-451-5477
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6609D24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	2.340 Inches Nominal
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Grip Diameter:	0.5605 Inches Minimum And 0.5615 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	1.500 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
iii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall Or Ams6322 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6609D24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.