

**Description**

Fastener Length: 2-13/32", Thread: 5/8-18, Thread Length: 59/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS661024                                 |
| Minimum Qty (MOQ):      | 2   |
| NSN:                    | 5306-01-132-5280                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6610-24 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.877 Inches Minimum And 0.927 Inches Maximum   |
| <b>Fastener Length:</b>                               | 2.387 Inches Minimum And 2.417 Inches Maximum   |
| <b>Head Style:</b>                                    | Dished Hexagon  |
| <b>Head Height:</b>                                   | 0.312 Inches Minimum And 0.327 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.928 Inches Minimum And 0.940 Inches Maximum   |
| <b>Grip Diameter:</b>                                 | 0.6230 Inches Minimum And 0.6240 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>                       | 0.625 Inches  |
| <b>Grip Length:</b>                                   | 1.490 Inches Minimum And 1.510 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 18  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas6610 Professional/Industrial Association Standard  |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6610-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.