



Military-Fasteners.com

P/N NAS6610-27Y

Description

Fastener Length: 2-19/32", Thread: 5/8-18, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS661027Y
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-365-4848
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6610-27Y Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.902 Inches Nominal
Fastener Length:	2.575 Inches Minimum And 2.605 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.312 Inches Minimum And 0.327 Inches Maximum
Width Between Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Shoulder Diameter:	0.6542 Inches Minimum First Shoulder And 0.6552 Inches Maximum First Shoulder
Shoulder Length:	1.678 Inches Minimum Overall And 1.698 Inches Maximum Overall
Nominal Thread Diameter:	0.625 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6610 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS6610-27Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.