

Description

Fastener Length: 1/4", Thread: 2-56, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6622LER4
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-399-0197
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS662-2LER4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.148 Inches Minimum And 0.221 Inches Maximum
Fastener Length:	0.220 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1010 Overall
Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/NAS662-2LER4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.