

**Description**

Fastener Length: 7/8", Thread: 2-56, Thread Length: 27/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6622R14
Minimum Qty (MOQ):	25
NSN:	5305-00-460-3397
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS662-2R14 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.773 Inches Minimum And 0.846 Inches Maximum
<b>Fastener Length:</b>	0.845 Inches Minimum And 0.875 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.156 Inches Minimum And 0.172 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 1010
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas662 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662-2R14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.