

**Description**

Fastener Length: 15/32", Thread: 2-56, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6622R7
Minimum Qty (MOQ):	80 EA
NSN:	5305-00-102-4560
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS662-2R7 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.372 Inches Minimum And 0.438 Inches Maximum
<b>Fastener Length:</b>	0.437 Inches Minimum And 0.474 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.143 Inches Minimum And 0.172 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 1010
<b>Screw Material Document And Classification:</b>	Astm A575 Assn Std Single Material Response Or Astm A576 Assn Std Single Material Response Or Astm A675 Assn Std Single Material Response Or Astm A108 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas662 Professional/Industrial Association Standard
<b>Departure From Cited Designator:</b>	As Modified By Matl

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662-2R7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.