

Description

Fastener Length: 3/8", Thread: 0-80, Thread Length: 11/32", NAS662 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS662C06
Minimum Qty (MOQ):	50
NSN:	5305-00-193-1074
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS662C0-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.295 Inches Minimum And 0.356 Inches Maximum
Fastener Length:	0.345 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.105 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 321 Or Steel Comp 347 Or Steel Comp 302 Or Steel Comp 303
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C0-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.