

Description

Fastener Length: 3/8", Thread: 0-80, Thread Length: 11/32", NAS662 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS662C06 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-193-1074 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS662C0-6 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.295 Inches Minimum And 0.356 Inches Maximum |
| Fastener Length: | 0.345 Inches Minimum And 0.375 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.105 Inches Minimum And 0.119 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.060 Inches |
| Thread Quantity Per Inch: | 80 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 321 Or Steel Comp 347 Or Steel Comp 302 Or Steel Comp 303 |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas662 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C0-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.