

Description

flat head

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS662C07 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-272-8305 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS662C0-7 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.383 Inches Minimum And 0.419 Inches Maximum |
| Fastener Length: | 0.408 Inches Minimum And 0.438 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.096 Inches Minimum And 0.119 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.060 Inches |
| Thread Quantity Per Inch: | 80 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 321 Or Steel Comp 347 Or Steel Comp 302 Or Steel Comp 303 |
| Screw Material Document And Classification: | Qq-s-763 Cl 8 Ty A Fed Spec 1st Material Response Or Qq-s-763 Cl 8 Ty A Fed Spec 2nd Material Response Or Mil-s-7720 Mil Spec 3rd Material Response Or Astm A582 Assn Std 4th Material Response |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas662 Professional/industrial Association Standard |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C0-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.